

IPC-HC1321 21.5 Inch Fanless Industry Panel PC



Features

- Configure 21.5 inches 400 nits high brightness TFT LCD, with LED backlight
- Capacitive multi-touch optional/anti-reflection protective glass
- Intel Core I7 CPU
- Rugged aluminum alloy frame design, fanless system, streamlined shell
- Design of wall-mounted installation, panel installation, and VESA installation
- Support 6*USB USB2.0, 6*COM RS232

Advantages

The equipment is suitable for hotels, restaurants, hospitals, shops, office buildings, companies and so on, can be used for information release, network wireless payment and so on.....

Specifications

	Front Bezel	NEMA 4 level strong protection, metal front baffle
	Display Type	21.5LED screen, option with 10.1LED screen
	Brightness (cd/m ²)	400 nits
	Display Color	262K



Fodenn Electronic Technology Co.,Ltd

Add: 3rd floor, Building B, Runchang industrial park, Zhonghao 2 road,
Bantian street, Longgang district, Shenzhen

Tel: 0755-86329789 Fax: 0755-83689236 Email: oversea1@fodenn.com

Display	Resolution	1920*1080 @ 60Hz
	Viewing Angle (H/V)	130°/140°
	Pixel Pitch	0.264 x 0.264 mm
	Aspect Ratio	16:9
	Contrast Ratio	400:1
	Response Time	25 ms
TOUCH Spec	Type	Multi-point capacitive touch.
	Transparency	80 ±3%
	Surface Hardness	≧ 3H (ASTM D3363, pressure 750g/45°)
	Knock test	Support 10,000,000 keystroke touches
Computer BOX Spec	Panel Material	Shell aluminum products
	Color	Black
	Coating	Coating spray paint
Motherboard Spec	CPU	Celeron J1900/3865U/J6412, Core 6-7th/10-11th gen U-series, Celeron/Pentium/Atom platform
	RAM	4GB (MAX 8Gb DDR3L)
	BIOS	64MB SPI Flash ROM
	Storage	1* 2.5" SATA HDD 1* MSATA SSD
	OS Support	WIN10/Linux
I/O Ports		2* USB2.0 + 4* USB2.0 (Front) (Can be customized 8-10usb) 6* RS232 1*DC Phoenix terminal 4PIN 1*HDMI+1*VGA 1* 8bit GPIO 2* LAN Intel 211 network card 1* Locking DC interface 1* Illuminated switch button
	Extension Port	1 * PCI-E mini, Can support Bluetooth/WIFI/4G/3G
	Power Supply	POWER DC IN: 100~240V AC-DC 60W Power adapter or DC type: 12VDC; power consumption 35W
Others	Size	525*317*60.4mm
	Net Weight	5.7kg
	Certificate	Comply with 3C standard
	Environment Temperature	Working temperature: -10°C~50°C Storage temperature: -20°C~85°C Vibration shock-work: 15G, 11ms duration

